



Typ "S"

Artikelnummer	Leiterquerschnitt (mm ²)
S1.5-U3	0.25 - 1.25
S1.5-U3.5	0.25 - 1.25
S1.5-U3.5-2	0.25 - 1.25
S1.5-U4	0.25 - 1.25
S1.5-U4-1	0.25 - 1.25
S1.5-U4-2	0.25 - 1.25
S1.5-U5	0.25 - 1.25
S1.5-U5-1	0.25 - 1.25
S1.5-U6	0.25 - 1.25
S1.5-U6-1	0.25 - 1.25
S1.5-U8	0.25 - 1.25
S1.5-U10	0.25 - 1.25
S1.5-U12	0.25 - 1.25
S2.5-U3	1.5 - 2.5
S2.5-U3.5	1.5 - 2.5
S2.5-U3.5-1	1.5 - 2.5
S2.5-U4	1.5 - 2.5
S2.5-U4-1	1.5 - 2.5
S2.5-U4-2	1.5 - 2.5
S2.5-U5	1.5 - 2.5
S2.5-U6	1.5 - 2.5
S2.5-U6-1	1.5 - 2.5
S2.5-U8	1.5 - 2.5
S2.5-U10	1.5 - 2.5
S2.5-U12	1.5 - 2.5
S6-U3.5	4 - 6
S6-U4	4 - 6
S6-U5	4 - 6
S6-U6	4 - 6
S6-U8	4 - 6
S6-U10	4 - 6
S6-U10-1	4 - 6
S6-U12	4 - 6
S6-U14	4 - 6
S6-U16	4 - 6