



Typ "A-L"

Artikelnummer	Leiterquerschnitt (mm ²)	Bolzen (Ø)	Leiterquerschnitt feindrähtig (mm ²)
A1-L6	6	6	
A2-L4	10	4	
A2-L5	10	5	
A2-L6	10	6	
A2-L8	10	8	
A2-L10	10	10	
A2-L12	10	12	
A3-L5	16	5	
A3-L6	16	6	
A3-L8	16	8	
A3-L10	16	10	
A3-L12	16	12	
A5-L4	25	4	
A5-L5	25	5	
A5-L6	25	6	
A5-L8	25	8	
A5-L10	25	10	
A5-L12	25	12	
A7-L6	35	6	25 - 35
A7-L8	35	8	25 - 35
A7-L10	35	10	25 - 35
A7-L12	35	12	25 - 35
A10-L8	50	8	35 - 50
A10-L10	50	10	35 - 50
A10-L12	50	12	35 - 50
A10-L16	50	16	35 - 50
A14-L8	70	8	50 - 70
A14-L10	70	10	50 - 70
A14-L12	70	12	50 - 70
A19-L8	95	8	70 - 95
A19-L10	95	10	70 - 95
A19-L12	95	12	70 - 95
A19-L14	95	14	70 - 95
A19-L16	95	16	70 - 95
A19-L20	95	20	70 - 95
A24-L8	120	8	95 - 120
A24-L10	120	10	95 - 120
A24-L12	120	12	95 - 120
A24-L14	120	14	95 - 120
A24-L16	120	16	95 - 120
A24-L20	120	20	95 - 120

Artikelnummer	Leiterquerschnitt (mm ²)	Bolzen (Ø)	Leiterquerschnitt feindrähtig (mm ²)
A30-L8	150	8	120 - 150
A30-L10	150	10	120 - 150
A30-L12	150	12	120 - 150
A30-L14	150	14	120 - 150
A30-L16	150	16	120 - 150
A37-L10	185	10	150 - 185
A37-L12	185	12	150 - 185
A37-L14	185	14	150 - 185
A37-L16	185	16	150 - 185
A37-L20	185	20	150 - 185
A48-L14	240	14	185 - 240
A48-L16	240	16	185 - 240
A48-L20	240	20	185 - 240
A60-L12	300	12	240
A60-L16	300	16	240
A60-L20	300	20	240