



Type "A-M"

Item number	Wire section (mm ²)	Wire section thin wires (mm ²)	Bolt (Ø)
2A3-M8	16	16	8
2A3-M10	16	16	10
2A5-M8	25	25	8
2A5-M10	25	25	10
2A5-M12	25	25	12
2A7-M8	35	25 - 35	8
2A7-M10	35	25 - 35	10
2A7-M12	35	25 - 35	12
2A10-M10	50	35 - 50	10
2A10-M12	50	35 - 50	12
2A10-M14	50	35 - 50	14
2A10-M16	50	35 - 50	16
2A14-M10	70	50 - 70	10
2A14-M12	70	50 - 70	12
2A14-M14	70	50 - 70	14
2A14-M16	70	50 - 70	16
2A19-M10	95	70 - 95	10
2A19-M12	95	70 - 95	12
2A19-M14	95	70 - 95	14
2A19-M16	95	70 - 95	16
2A19-M20	95	70 - 95	20
2A24-M10	120	95 - 120	10
2A24-M12	120	95 - 120	12
2A24-M14	120	95 - 120	14
2A24-M16	120	95 - 120	16
2A24-M20	120	95 - 120	20
2A30-M10	150	120 - 150	10
2A30-M12	150	120 - 150	12
2A30-M14	150	120 - 150	14
2A30-M16	150	120 - 150	16
2A30-M20	150	120 - 150	20
2A37-M12	185	150 - 185	12
2A37-M14	185	150 - 185	14
2A37-M16	185	150 - 185	16
2A37-M20	185	150 - 185	20
2A48-M12	240	185 - 240	12
2A48-M14	240	185 - 240	14
2A48-M16	240	185 - 240	16
2A48-M20	240	185 - 240	20
2A60-M12	300	240 - 300	12
2A60-M14	300	240 - 300	14

Item number	Wire section (mm2)	Wire section thin wires (mm2)	Bolt (Ø)
2A60-M16	300	240 - 300	16
2A60-M20	300	240 - 300	20
2A80-M12	400	300 - 400	12
2A80-M14	400	300 - 400	14
2A80-M16	400	300 - 400	16
2A80-M20	400	300 - 400	20
2A100-M16	500	400	16
2A100-M20	500	400	20
2A120-M16	630	500	16
2A120-M20	630	500	20
2A160-M20	800	630	20
2A200-M20	1000	800	20