



Tipo "T-M"

Codice articolo	Sezione cavo (mm ²)	Sezione cavo flessibile (mm ²)	Bullone (Ø)
T4-M4	4	4	4
T4-M5	4	4	5
T4-M6	4	4	6
T6-M4	4 - 6	4 - 6	4
T6-M5	4 - 6	4 - 6	5
T6-M6	4 - 6	4 - 6	6
T6-M8	4 - 6	4 - 6	8
T10-M5	10	10	5
T10-M6	10	10	6
T10-M8	10	10	8
T10-M10	10	10	10
T16-M5	16	16	5
T16-M6	16	16	6
T16-M8	16	16	8
T16-M10	16	16	10
T25-M6	25	25	6
T25-M8	25	25	8
T25-M10	25	25	10
T25-M12	25	25	12
T35-M6	35	35	6
T35-M8	35	35	8
T35-M10	35	35	10
T35-M12	35	35	12
T50-M6	50	50	6
T50-M8	50	50	8
T50-M10	50	50	10
T50-M12	50	50	12
T70-M8	70	70	8
T70-M10	70	70	10
T70-M12	70	70	12
T95-M8	95	95	8
T95-M10	95	95	10
T95-M12	95	95	12
T95-M14	95	95	14
T95-M16	95	95	16
T120-M8	120	120	8
T120-M10	120	120	10
T120-M12	120	120	12
T120-M14	120	120	14
T120-M16	120	120	16
T150-M10	150	150	10

Codice articolo	Sezione cavo (mm2)	Sezione cavo flessibile (mm2)	Bullone (Ø)
T150-M12	150	150	12
T150-M14	150	150	14
T150-M16	150	150	16
T185-M10	185	185	10
T185-M12	185	185	12
T185-M14	185	185	14
T185-M16	185	185	16
T240-M10	240	240	10
T240-M12	240	240	12
T240-M14	240	240	14
T240-M16	240	240	16
T240-M20	240	240	20
T300-M10	300	300	10
T300-M12	300	300	12
T300-M14	300	300	14
T300-M16	300	300	16
T300-M20	300	300	20
T400-M16	400	400	16
T400-M20	400	400	20